

VI. COST ESTIMATES

The VLB Array is a complex sophisticated system which is based on well understood techniques and instrumentation whose cost can be reliably estimated. No new sophisticated structural engineering is involved; designs exist for most of the electronic systems, and in many cases prototypes are already in operation on existing radio telescopes. Nevertheless, further design and engineering will be required to ensure that all sub-systems take advantage of the latest advances in the art, particularly in the rapidly evolving digital field. Indeed, experience has shown that the instrumentation will continually be modified and improved, and allowance for these improvements forms a crucial part of the operating budget.

~~In this chapter we describe the total construction and operating costs.~~
We also include in this chapter a preliminary construction plan. All costs are given in thousands of dollars (1982).

A. Array Elements

Estimates for the construction and acquisition of new equipment is, in part, based on the cost of similar instrumentation in use or being fabricated for the VLA or other NRAO telescopes with allowances for escalation to 1982 as well as required design changes.

1. The Antenna Elements. Twenty-eight antennas have been built and are now in operation at the VLA. The price for a VLA type antenna modified to meet the specifications discussed in Section III-C has been determined from this base with the following corrections:

- a) The increased cost of steel and labor due to price escalation since the original contract.

- b) The increased erection costs due to the use of Union labor and lack of the NRAO supplied erection facility.
- c) Shipping costs of structure to the site.
- d) Manufacturer's loss on VLA antennas and profit allowance.
- e) Shielding and insulating of pedestal structure.
- f) Strengthening of "feed" legs.
- g) Strengthening of yoke structure.
- h) Higher accuracy surface panels.

In addition, there is a one time only engineering cost of 585 K made necessary by the various modifications which are required, and 115 K for tooling.

In this way we estimate a total cost of \$17,490 K for ten antennas, delivered over a two year period.

We have not yet completed the cost analysis of the new wheel-and-track design. The cost of this antenna is reduced due to the simplicity of the structure, that is, fewer joints and fewer members are used. But this may be partially offset by the need to adopt a new design concept. There is also an increased engineering and design cost, but this is small if it is amortized over 10 antennas.

For our budget calculations we have assumed the use of modified VLA type antennas to arrive at a total cost of \$17,490 K. We anticipate, however, that the Array will be built using the wheel-and-track concept, and we have therefore allowed for the \$950 K necessary for the full engineering design of this antenna. However, the total cost of design plus fabrication of the 10 wheel-and-track antennas should not exceed the estimated cost of the modified VLA antennas, and is expected to give improved performance at the shorter wavelength. In addition to the basic antenna structure, the non-manufacturer supplied items in Table VI-1 are added

TABLE VI-1

ADDITIONAL ANTENNA COMPONENTS

1) Feed mounting ring (vertex room cover) and feed support towers	12 K
2) Subreflector and support structure	22
3) Focus and subreflector rotation mount	25
4) Electrical installation	<u>4</u>
TOTAL Auxiliary Antenna Equipment	63 K

To this must be added a non-recurring engineering and tooling cost of 90 K.

2. Feed System. The cost of the 10 band feed system is given in Table VI-2.

TABLE VI-2

FEED SYSTEM

<u>Prime Focus Feeds</u>		
327 MHz	2 K	
610	<u>2</u>	
TOTAL		4 K
<u>Secondary Focus Feeds</u>		
1.5 GHz	13 K	
2.3	11.7	
5.5	3.6	
8.4	1.8	
10.7	1.8	
15	1.5	
22	1.5	
44	<u>1.5</u>	
TOTAL		36.4
Polarizers		8
S/X Band Dichroic		10
Windows, Waveguides, etc.		4
Measurement and Test		<u>20</u>
TOTAL Feed System (per ant.)		82.4 K
Non-recurring Engineering and Development		
Materials		150 K
Labor		110 K

TABLE VI-3
FRONT END COSTS

<u>Cryogenic Costs</u>		<u>Materials \$ K</u>	<u>Labor</u> (Man Months)
<u>20° K Cryogenics</u>			
Refrigerators	6x6 K	36 K	
Compressors	3x8 K	24	
<u>4° K Cryogenics</u>			
Refrigerator and Compressor		50	
<u>Helium Lines</u>			
4 K and 20 K Systems		20	
Total Cryogenics			130 K
<u>300° K Front End Costs</u>			
327 and 610 GASFETS Dual Pol.	4x1 K	4 K	2
Weatherized Package	2x0.5 K	1	
Buffer Amplifiers	4x0.25 K	1	2
Assembly		16	
Total 300 K Front Ends			22
<u>20° K Front End Costs</u>			
Dewar, Input Lines, etc.		20 K	6
GASFET Amplifiers at 1.5, 2.3, 5.5 8.4, 10.7 and 15 GHz			
6 frequencies x 2 Polariz		12	6
Mixer/IF Amplifiers (12)		12	
Local Oscillator System		25	6
Assembly		56	
Total 20 K Front Ends			120
<u>4° K Front End Costs</u>			
Dewar, Input Lines, etc.		20 K	6
Dual Channel Masers 22, 43 GHz		20	12
Solid State and Plystron Pumps		20	
Local Oscillator System		10	6
Mixer/IF 4x2.5		10	
Assembly		64	
Total 4 K Front Ends			144
<u>Miscellaneous</u>			
System Noise Calibration		15 K	
Phase Calibration		15	
Power Supplies, etc.		10	
Total Miscellaneous			40
TOTAL FRONT END SYSTEM PER ANTENNA			456 K

3. Front End System. The cost of parts and labor for the multi-frequency front end system is summarized in Table VI-3.

Because most of the individual receiver elements (e.g. cooled FET amplifiers, 1.3 and 0.7 cm masers) have already been developed or are part of ongoing programs at the NRAO, we anticipate that only a further 150 K of non-recurring engineering and prototyping will be required to develop the complete 10 band low noise receiver system.

4. Hydrogen Maser

We have obtained cost estimates for hydrogen masers from three potential suppliers. These ranged from 2100 K to 4050 K per unit as summarized below. Supplier No. 1 offered no quantity discount and did not consider selling the physics package alone. Supplier No. 2 estimated a 25% cost saving if 10 units are procured at the same time, and a further reduction of \$75 per unit if the receiver/synthesizer system is omitted. The third estimate is based on a formal quotation for purchase of one unit in 1982 either with or without the receiver system.

We have also considered developing the maser oscillators in house, but have rejected this as being impractical. However, since we are able to build the receiver/synthesizer system for about 1/2 of the cost of a commercial supplier, we intend to purchase the "physics package" alone from an outside supplier. We estimate the cost of the hydrogen maser oscillator in Table VI-4 below.

TABLE VI-4

Hydrogen Maser Physics Package	210 K
Receiver Synthesizer (Materials)	18
Receiver Synthesizer (Labor)	22
TOTAL Hydrogen Maser (per ant.)	250 K
Receiver Development	30 K

5. The Record System. The cost of the data acquisition system is based on modified Video Cassette Recorders and the recorder rack plus one spare rack each complete with recorders and electronics. Although only one record rack per station is required for normal operation, the second recorder allows for uninterrupted operation in case of failure of the electromechanical cassette changer, or in special cases to record with twice the normal bandwidth. This option, however, requires two passes through the Processor.

The data acquisition system consists of the IF system, the Data Digitization Electronics, and the Record System. The cost is summarized in Table VI-5 below.

TABLE VI-5

COST OF DATA ACQUISITION SYSTEM

IF Switching Matrix	5 K	
IF Processor	36	
IF to Video Converters	12	
TOTAL IF System		53 K
Sampler	2 K	
RS232 Distributor	1	
Delay Calibrator	3	
Rack, Power Supplies, Connectors, etc.	10	
5 MHz Distributor	2	
Assembly (8 man months)	21	
SUBTOTAL Data Digitation Electronics		39
18 video cassette recorders	15 K	
2 recorder racks with electronics	36	
Assembly and integration (0.25 man yrs)	7	
TOTAL Recorder Racks		58
TOTAL DATA ACQUISITION SYSTEM (Per Ant.)		150 K

A one time non recurring cost of design, development, and documentation of the recorder/playback system is estimated to be 130 K including 29 K for materials.

6. Control and Monitor System. Each antenna element has its own minicomputer system which receives control information from the Array Control Computer and transmits data to monitor the front end and record system performance as well as meteorological data. The cost of the Array Control Computer is given in Section VI B2. The per antenna cost is shown in Table VI-6 below.

TABLE VI-6

COST OF TELESCOPE CONTROL AND MONITOR SYSTEM

Telescope Control Computer	30 K
(Includes 128k byte memory, two 10M byte disks, tele-typewriter, CRT, and manufacturer's operating system and communications software)	
Interface Equipment to Antenna and Receiver	5
(Three data-sets and serial interface to computer)	
Fringe Verification Buffer	3
(256k byte memory)	
Communication Equipment - Modems	5
Dedicated Test Equipment	5
Spare Computer Parts	6
Installation Cabling (\$1,000) and 1/2 man-year check-out labor	16
TOTAL per antenna	70 K

7. Site Development. The following items are included at each of the Array Stations.

- a) Site acquisition and grading 5 K
- b) Control building, including environmentally controlled area for instrumentation and computers, tape storage, shipping area, office space, maintenance area, and toilet.
1400 sq. ft. at \$70 per sq. ft. 98

c) Telescope foundations. Cost varies from site to site depending on terrain, etc.	50 K
d) Emergency generator. 30 KVA to stow antenna and keep cryogenics running.	20
e) Roads. Road requirements will vary from site to site but is taken to average 400 ft. A 12' wide road for light traffic can be constructed for \$30 per foot including typical excavation and grading costs.	12
f) Electrical power installation. 400-ft from commercial power. Underground installation at \$15 per ft.	6
g) Water supply and disposal system	10
h) Furniture	6
i) Maintenance equipment including small 4-wheel drive vehicle with snow plot, tools, service elevator.	35
j) Fence (approx. 1,200 sq. ft.) at \$12/sq. ft.	12
k) Soil tests	6
l) Design fee (engineer-architect)	25
<hr/>	
TOTAL Site Development (per site)	285 K

8. Other Site Development. The following additional items are required at each antenna element.

a) Test equipment and miscellaneous tools	35 K
b) Water vapor radiometer and other meteorological sensors.	35
c) Timing equipment. Rubidium clock and timing receivers.	40
d) Test and Installation of all station feed and electronic systems.	10
<hr/>	
TOTAL Other Equipment (per antenna)	120 K

B. Operations Center

1. The Playback Processor consists of the control computer, the tape playback system, and the correlator. The cost estimate in Table VI-7 is based on the VLA type recirculating correlator.

TABLE VI-7
PLAYBACK PROCESSOR

<u>Computer System</u>		
CPU with 2 Mbyte Memory, 100 Mbyte Disk, 800/1600 BPI Type Drive, Operations Software	182 K	
2 Tape Drives 6250 BPI	67	
Array Processor, 64 K Word Memory	73	
4 Text, 1 Graphics Terminals	10	
Cabinets, Power, Furniture	10	
Software Development (3 man years)	96	
Installation (0.1 man years)	4	
Subtotal Computer		442 K
<u>Tape Playback Unit</u>		
16 Playback Racks	288 K	
140 Video Cassette Recorders	112	
Assembly (2 man years)	64	
Subtotal Tape Playback Unit		464
<u>Correlator System</u>		
Correlator Hardware	530 K	
Support Hardware	200	
Design (3 man years)	96	
Assembly (2 man years)	64	
Subtotal Correlator System		898
System Integration (2 man years)		62
TOTAL PLAYBACK PROCESSOR		1,858 K
Development (2 man years)		64 K

2. Computing Equipment.

Processor Controller. The cost of the on-line computer which controls the Processor and handles some of the preliminary fringe fitting is included in the cost of the Processor.

Array Control Computer. Control of the Array and communications with the station computers will be through the Central Array Control Computer. An extra Telescope Control Computer is included at the Operating Center for programming support. Cost of the Control System is:

Array Control Computer	204 K
(Includes 512k byte memory, two 1600/6250 bpi tape drives, two 122M byte disks, tele-typewriter, printer, card reader, 2 graphics and 8 text CRT;s, and manufacturer's software for operating system, communications, and FORTRAN)	
Communication Equipment - Modems	15
Telescope Control Computer	35
(For software development)	
Software (16 man-years)	<u>512</u>
	<u>766 K</u>
TOTAL Control and Monitor System - Central Control	766 K

Post Processing. Post processing requirements are outlined in Section IV-B in terms of the DEC VAX-11/780 system. Post processing software will depend largely on procedures already developed for the VLA and existing specialized VLBI software. An additional 10 man-years of programming effort is assumed. Cost estimates are given below:

4	VAX-11/780 with 2 Mbyte memory,	800 K
4	Additional 2 Mbyte memory	70
	Disks and Controllers (16G Bytes)	550
9	Array Processors	310
2	I ² s Image Displays	140
2	Printers	30
12	CRT terminals (9 text, 3 graphics)	30
6	High Density Tape Drives	170
	Optical Disk	40
	Video Disk	20
	DECNET System	30
	Misc.	50
<hr/>		
	Total Post-Processing Hardware	2240 K
	Post-Processing Software Development (10 man-years)	320 K
<hr/>		
	TOTAL Post Processing Cost	2560 K

3. Control Building. The control building houses the Playback Processor, the Array Control System, the computer for data reduction, electronic laboratories for development and maintenance, storage area for magnetic tapes and spare parts, office space for visitors and staff, and shipping area. 10000 sq. ft. are required at \$80 per sq. ft. which includes design fee and utility service connections at an existing operating site.

CONTROL BUILDING	800 K
------------------	-------

4. Magnetic Tapes. At the normal continuum bandwidth of 50 MHz, 42 tapes per day are used at each station. For most spectroscopic applications,

the number of tapes used will be very much less, while for some continuum observations, two recorders will be used to increase the bandwidth. We have allowed for a 60 day supply of tapes at an average of 42 tapes per day to arrive at a cost estimate of tapes and shipping bins.

MAGNETIC TAPES AND BINS

450 K

5. Other Operating Equipment. Funds are allocated for general and digital test equipment and for a precision Cs flying clock whose "mean time

OTHER OPERATING EQUIPMENT

200 K

6. Spare Parts. The major portion of spare parts stock will be located at the Service Centers with only small components whose failure rate is fairly high being maintained at each field site. Those parts whose "mean time between failure" is greater than one year or whose failure will not bring down an entire antenna system (e.g. a single receiver module) will be stocked only at the Service Center. We estimate the following costs for spare parts in order to support and maintain operation with an average downtime less than 5 percent at each telescope.

The spare parts inventory includes the approximate equivalent of one front end, IF, digitization, and hydrogen maser system as well as the recorder and computer spares stocked at the telescopes and listed earlier.

TABLE VI-8

SPARE PARTS INVENTORY

Antenna structure and servo	330 K
Cryogenics	45
Receiver	500
Hydrogen Maser	150
Computer	300
TOTAL Spare Parts	1450 K

VLB ARRAY

COST SUMMARY (K\$)

Per Station Systems

Antenna	1654
Aux. Antenna Equipment	63
Feeds	82
Front Ends	456
Record System	150
Control and Monitor	70
Frequency Standard	250
Site Development	255
Other Equipment	120
Total per station	3100

SUBTOTAL 10 STATIONS

31000

Central Laboratory

Control System	736
Playback System	464
Processor	1370
Post Processing (incl. software)	2500
Building and Site	850
Operating and test equipment	200
Spares	1450
Tapes	450

SUBTOTAL CENTRAL LABORATORY

8020

Development

Antenna	950
Aux. Antenna Equipment	90
Feeds	260
Control	30
Front End	150
Record System	130
Site Evaluation	300
Frequency Standard	30
Processor	60
Post Processing	60

SUBTOTAL DEVELOPMENT

2060

PROJECT MANAGEMENT

2000

CONTINGENCY

6000

TOTAL

49080